

EL888270903US

PATENT

Docket No. 150.0088 0102

METHODS FOR FORMING ROUGH RUTHENIUM-CONTAINING

LAYERS AND STRUCTURES/METHODS USING SAME

please insert
*This is a divisional of patent Application serial number 09/589,849,
filing date 6/8/2000 (PAT NO 6,429,127).*

Field of the Invention

5 The present invention relates to semiconductor devices and the fabrication thereof. More particularly, the present invention pertains to rough conductive layers of ruthenium and/or ruthenium oxide.

*PD
12/11/03*

Background of the Invention

10 In the fabrication of integrated circuits, various conductive layers are used. For example, during the formation of semiconductor devices, such as dynamic random access memories (DRAMs), conductive materials are used in the formation of storage cell capacitors and also may be used in interconnection structures, e.g., conductive layers of contact holes, vias, etc.

15 As memory devices become more dense, it is necessary to decrease the size of circuit components forming such devices. One way to retain storage capacity of storage cell capacitors of the memory devices and at the same time decrease the memory device size is to increase the dielectric constant of the dielectric layer of the storage cell capacitor. Therefore, high dielectric constant materials are used in
20 such applications interposed between two electrodes. One or more layers of various conductive materials may be used as the electrode material.

 Further, to the increase the capacitance for a storage cell capacitor of a memory device without increasing the occupation area of the storage cell capacitor, various techniques have been used to increase the surface area of the lower
25 electrode of the capacitor. For example, hemispherical grains (HSG) have been used to enhance such surface area of the lower electrode of a capacitor of a memory device.